

Technical Data Sheet

Pb 5550T – Double Coated tissue tape

➤ **Description**

Double-sided adhesive tape. The product compliant by RoHS (2011/65/EU, 2015/863)

➤ **Carrier**

Cellulose 14 gr/m, tissue paper

➤ **Liner**

Siliconised paper Havana or White 80 g/m²

➤ **Adhesive**

Modified Acrylic High Tack

➤ **Area of use**

Lamination of materials like PE or PE foams for permanent bonding with high strength performance requirements. Application on porous materials. Specially recommended for polyurethane Foam lamination. Pb 5550T is also recommended for high adhesion performance on painted wood and / or metal surfaces, glass surfaces, textile surfaces, felt, sponge and rubber surfaces. In order to obtain high performance, the bonding surfaces should be protected against moisture, oil, dirt, dust, rust etc. residue.

➤ **Technical Data**

Thickness	80 micron
Temperature resistance***	From -40° C, up to 90 °C Long term
Loop Tack* AFERA 5001	28,2 N/25 mm (+-2)
Colour	Light white
Shelf life	12 months, in closed original packing. At temperature of 21°C and a relative humidity of 50%. The quality and durability of the tape may vary according to temperature and humidity. Low temperatures can increase the risk of condensation, consequently reducing the tack of the self-adhesive product

PROFIBOND Slovakia, s.r.o.

Office: Mlynská 694/2, Stropkov, 091 01

GSM: + 421 948 784 464

mail: profibond@profibond.sk

web: www.profibond.sk