



Technical Data Sheet

Pb 2075T – Double Coated PET mesh tape

➤ **Description**

Double-sided adhesive tape.

➤ **Carrier**

Multidirectional polyester textile mesh – rectangular

➤ **Liner**

Siliconised paper Havana 80 g/m²

➤ **Adhesive**

Modified Acrylic High Tack

Free from plasticizers and heavy metals. Meets RoHs specifications.

➤ **Area of use**

Lamination of materials requiring longitudinal or transversal stretch. Application on porous materials. Specially recommended for polyurethane Foam lamination. Pb 2075T is also recommended for high adhesion performance on painted wood and / or metal surfaces, glass surfaces, textile surfaces, felt, sponge and rubber surfaces. In order to obtain high performance, the bonding surfaces should be protected against moisture, oil, dirt, dust, rust etc. residue.

➤ **Technical Data**

Thickness	80 micron
Temperature resistance***	From -40° C, up to +100 °C Short term: 120°C
Loop Tack* AFERA 5001	27,3 N/25 mm (+-2)
Colour	Transparent
Shelf life	12 months, in closed original packing. At temperature of 21°C and a relative humidity of 50%. The quality and durability of the tape may vary according to temperature and humidity. Low temperatures can increase the risk of condensation, consequently reducing the tack of the self-adhesive product

PROFIBOND Slovakia, s.r.o.

Office: Mlynská 694/2, Stropkov, 091 01

GSM: + 421 948 784 464

mail: profibond@profibond.sk

web: www.profibond.sk