



Technical data sheet

## Pb 50560 Special density Protective film

### Description

Pb 50560 is car protective film made of special density PE (polyethylene plastic). It is specifically designed to protect decorative surfaces such as spray painted bumpers. Film is high puncture resistance and high transmitting, moisture proof.. Easy to be laminated and peeled off.

### Carrier

PO (polyethylene plastic)

### Adhesive

PIB film

### Area of use

Mainly used in automotive industry to protect parts from dust and scratches during assembly, transportation and storage

### Technical Data

Total thickness	57 µm
Temperature resistance***	up to 60° C
Tensile strength* AFERA 5001	PIB
Colour	White
Shelf life	12 months, in closed original packing. At temperature of 21°C and a relative humidity of 50%. The quality and durability of the tape may vary according to temperature and humidity. Low temperatures can increase the risk of condensation, consequently reducing the tack of the self-adhesive product

\*Note: Values should be used for specification purposes and are averages taken from PSTC, ASTM or AFERA test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Profibond tapes serves you better. Contact our team for qualified application support.

### PROFIBOND Slovakia, s.r.o.

Office: Mlynská 694/2, Stropkov, 091 01

GSM: + 421 948 784 464

mail: [profibond@profibond.sk](mailto:profibond@profibond.sk)

web: [www.profibond.sk](http://www.profibond.sk)