



Technical data sheet

Pb7010 Warning tape

Description

Soft PVC warning tape, made of PVC film coated with a layer of corrosion-resistant natural rubber. Moderate stickiness and unwinding force are easy to handle. Has excellent windability, wear resistance, acid resistance, alkali resistance, oil resistance and other characteristics. Applicable to warning area signs.

Carrier

PVC film

Adhesive

Natural rubber

Area of use

Warning and Hazard floor tapes to highlight walkways and hazardous areas effectively within the workplace. Applicable to warning area signs.

Technical Data

Total thickness	0.13 mm
Temperature resistance***	From -40°C to +80°C
Tensile strength* AFERA 5001	≥35N/25mm
Colour	Orange
Shelf life	12 months, in closed original packing. At temperature of 21°C and a relative humidity of 50%. The quality and durability of the tape may vary according to temperature and humidity. Low temperatures can increase the risk of condensation, consequently reducing the tack of the self-adhesive product

*Note: Values should be used for specification purposes and are averages taken from PSTC, ASTM or AFERA test methods. The company does not warranty performance in specific applications. Since product performance may vary, each user should conduct their own test to determine the products fit for use in specific applications. The purchaser shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (20°C) with 50% relative humidity. Profibond tapes serves you better. Contact our team for qualified application support.

PROFIBOND Slovakia, s.r.o.

Office: Mlynská 694/2, Stropkov, 091 01

GSM: + 421 948 784 464

mail: profibond@profibond.skweb: www.profibond.sk